



8-Port HDMI KVM Switch

Eight HDMI and Eight USB-B Ports, Full HD, set of eight USB cables included

Part No.: **152785**

EAN-13: 0766623152785 | UPC: 766623152785

The Manhattan 8-Port HDMI KVM Switch provides excellent functionality for today's multimedia SOHO environment, allowing for seamless HDMI signal switching between eight PCs or other HDMI-enabled devices. Through effectively sharing one keyboard and mouse among eight connected computers, the 8-Port HDMI KVM Switch offers independent switching via front panel buttons or through keyboard and mouse hotkeys.

Features:

- Allows for management and control of eight HDMI or USB computers from one keyboard, monitor and mouse
- PC hot-plug capability for maintenance without having to power down the KVM switch or PCs
- Channel selection via push buttons and keyboard or mouse hotkeys
- Supports screen resolutions of up to 1920 x 1440
- Supports Windows, Linux, Unix and MAC OS
- Set of eight USB control cables included
- Three-year warranty

Specifications:

Standards

- USB 1.1
- HDMI
- FCC
- CE

Certifications (Power Supply)

- UL

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- SAA

General

- PC connections: eight
- Console connections: one
- Console port connectors:
 - Eight USB Type-B (female)
 - Eight HDMI (female)
- Computer selection:
 - Via buttons
 - Via hotkeys (mouse or keyboard)
- Video resolution: max. 1920 x 1440
- Latency in switching between sources: 3-5 seconds

LEDs

- One LED per channel

Power

- External power adapter: DC 12.0 V, 2.0 A
- Power consumption: max. 5.0 W

Physical

- Dimensions: 140.3 (L) x 481 (W) x 43.7 (H) [mm] / 5.52 (L) x 18.94 (W) x 1.72 (H) [in]
- Weight: 1.85 kg (4.08 lbs.)
- Metal housing

Environmental

- Operating temperature: 0 – 40°C (32 – 104°F)
- Storage temperature: -20 – 60°C (-4 – 140°F)
- Operating humidity: 20 – 90% RH, non-condensing

Package Contents

- 8-Port HDMI KVM Switch
- Set of eight USB control cables included
- Power supply
- User manual
- Two mounting brackets and screws



