



# kramer

## VP-200N5

1:2 Computer Graphics Video Distribution Amplifier

| VGA/UXGA - 15-pin HD



The VP-200N5 is a distribution amplifier for computer graphics signals up to and exceeding UXGA. The unit takes one input, provides correct buffering and isolation, and distributes the signal to two identical outputs

## FEATURES

High Bandwidth - 370MHz (-3dB)

HDTV Compatible

**Kr-isp® Advanced Sync Processing** - Ensures compatibility with a wide range of computers (even if the sync level is too low) by restoring the sync signal waveform. Kr-isp® advanced sync processing can be enabled or disabled

**EDID PassThru** - Passes EDID signals from source to display (from input to output 1 only)

DC Coupling

3ft 15-pin HD Cable Included

Sold in Cartons of 10

**Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter



# kramer

## TECHNICAL SPECIFICATIONS

---

INPUT:	1 UXGA on an 15-pin HD connector
OUTPUTS:	2 UXGA on 15-pin HD connectors
MAX. OUTPUT LEVEL:	1.8Vpp
BANDWIDTH (-3dB):	370MHz
DIFF. GAIN:	0.03%
DIFF. PHASE:	0.03Deg
K-FACTOR:	<0.05%
S/N RATIO:	71dB @5MHz
COUPLING:	DC
POWER CONSUMPTION:	5V DC, 76mA
INCLUDED ACCESSORIES:	Power supply (5V/2.6A), molded 15-pin HD (M) to 15-pin HD (M) VGA cable C-GM/GM-3, mounting bracket
OPTIONS:	RK-3T 19" rack adapters
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.2kg (0.4lbs) approx
Shipping Dimensions	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50" ) W, D, H
Shipping Weight	0.7kg (1.5lbs) approx

