



RC-43SL

6-button Touch-Sensitive Ethernet Control
Keypad (US)

| Ethernet - RJ-45



The RC-43SL is a touch-sensitive 6-button control keypad. Connected over Ethernet to Site-CTRL™ remote AV control, site management & monitoring system, as well as LAN-connected control gateways for extended controlled devices capacity. It also connects over KNET™ to master room controller and auxiliary keypads for remote keypad control. It can flexibly serve either as a standalone room controller, part of multi-units KNET™ system, or part of multi-unit Ethernet system managed by Kramer Site-CTRL™ site management platform. The RC-43SL is ideal for auditoriums and meeting rooms, for convenient control of their complex multimedia systems and other room facilities such as screens, lighting and shades

FEATURES

- Touch-Sensitive & Label Capable Buttons** - 6 white-color LED-feedback buttons
- Custom Labeled, Removable Button Caps**
- 1 K-NET™ Connector** - Connect to master room controller, and auxiliary keypads for remote keypad control
- K-NET™ Single Link Connection** - Provides a single keypad link cable-connectivity, carrying both power and keypad control
- 2 RS-232 Bi-directional Control Ports** - Control a device via bi-directional serial control protocols
- 2 IR Emitter Control Ports** - Control a device via IR control protocols
- 3 Relay Control Ports** - Control a device via Relay Contact Closure, such as scrolling up and down screens, drapes, shades, and blinds
- IR Sensor Port** - Learns commands from IR remotes
- Program Control** - Program configuration with Kramer K-Config software
- Kramer Site-CTRL™ Compatibility** - For network management and remote control over the Ethernet port
- Mini USB Port** - To upload configuration files, set the K-NET™ ID number, and power the device during configuration
- Mounting** - In-wall, in standard 1 gang US wall junction boxes
- Easy Installation** - Fits to standard in-wall boxes for simple and cost-reducing installation



TECHNICAL SPECIFICATIONS

PORTS:	2 RS-232 and 1 K-NET on terminal block connectors, 1 Ethernet on an RJ-45 connector, 1 infrared sensor, 1 Mini USB for programming
OUTPUTS:	2 IR-out and 3 relays (36V AC or DC, 2A, 60V AC maximum on non-inductive load) on terminal block connectors
POWER CONSUMPTION:	12V DC, 100ma
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power supply, mounting frame, labeled caps set, screwdriver
Product Dimensions	US: 6.90cm x 3.50cm x 11.43cm (2.72" x 1.38" x 4.50") W, D, H
Product Weight	US: 0.1kg (0.2lbs) approx
Shipping Dimensions	US: 25.60cm x 11.80cm x 11.40cm (10.08" x 4.65" x 4.49") W, D, H
Shipping Weight	US: 0.7kg (1.6lbs) approx



CONFIGURATIONS

RC-43SL	US-size RC-43SL, White + Black Design Frames, PSU + Power cord, Labeled Caps Set, Screwdriver
RC-43SL/JP	US-size RC-43SL, White + Black Design Frames, PSU + Japan Power cord, Labeled Caps Set, Screwdriver

