


1, Patchcord Length (m)

Length L	Tolerance T	Part No	Packing Bag Size
L = 1.0m	±0.10m	470001	180x280mm
L = 2.0m	±0.10m	470018	180x280mm
L = 3.0m	±0.10m	470025	180x280mm

2, Connector Test Specifications

Parameters	Specifications
Insertion Loss	≤0.30dB
Return Loss	≥35.0dB
Durability(1000Mating)	0.2dB Max.Increase
Operating Temperature	-40℃~75℃
Storage Temperature	-40℃~85℃

Cable Profile View



ITEM	DESCRIPTION	Q'TY
1	SC Dust Cap (Clear)	4
2	SC/UPC Connector MM Duplex 3.0mm (Beige)	2
3	SC Duplex Clip (Beige)	2
4	SC 3.0 Boot (Red)	2
5	SC 3.0 Boot (Black)	2
6	MM Duplex 50/125 3.0mm LSZH Cable(Orange)	Xm



DRAWN BY	LW	SPEC.	SC/UPC-SC/UPC MM-Duplex 50/125 3.0mm Patchcord L=Xm, LSZH Orange Jacket			A
CHECK BY	ZH	CUSTOMER	SHEET	/P	SCALE	NONE UNIT: mm
APPD. BY	ZH	DWG. NO.	DATE	2015-04-07	VIEW	